

secure your family • secure your properties



SPEED DOME CAMERA



Securematic C918/SS22M Speed Dome

Image Inductor : 1/4" Color CCD
Effective Pixels : 752H x 582V (440000pixels) PAL
Synchronous System : Internal Synchronization
VF Output : Compound Signal : 1.0Vp ~ p/75 ϕ
White Balance : Automatic / Manual
Power Supply : DC15V \pm 10% 1.5A
Power Consumption : 15VA Weight : 2Kg
Mounting Style : Ceiling or ceiling hanging style
Relative humidity : 10 ~ 75% (under no condensing)
Operation temperature : 0 °C ~ 40 °C
Scan System : 15.625KHz(H) 50Hz (V)
Horizontal Resolution : 480TV lines
Signal / Noise ratio : Larger than 48db
Electronic Shutter : 1/3 ~ 1/10,000 seconds
Lowest Temperature : 0.01 ~ 1Lux (F1.6)
Zooming Range : 16 ,18 ,22 ,23 ,25times optical
zooming and times electronic
zooming
Iris : Automatic / Manual
Zooming : Automatic / Manual
Horizontal Turning : 80 ° /s
Vertical Turning : 40 ° /s
Preset Positions : 64 positions
Patrol Function : 6 patrol channels in maximum

Securematic C918/SS22WH High Speed Dome

Power Supply : AC24V 50/60Hz
Power consumption : Indoor dome : 15W
Outdoor dome : 35W
Sync system : Internal / External selectable
Preset : 128 presets
Auto tour : 6 Pattern : 40s
Alarm : 4 channels input & 1 channel output
Privacy masking : 6 (some model only)
Zoom-rotation Interaction : Control speed
auto adjust
according to the
focus length
Auto flip : Rotate 180° when camera tilts to
the vertical position
Auto pan scan : 360°
Programmable Pan speed : 0° ~ 300° /s
Pan rotation range : 360° continues
Tilt range : Tilt 90°
Tilt speed : 0° ~ 120° /s
Control mode : RS485
Baud Rate : 2400/4800/9600/19200 bps
Fan & heater : Fan & heater auto-start
(only outdoor dome)
Environment temp : Indoor dome : 0 °C ~ +40 °C
Out door dome : -35 °C ~ +55 °C

Securematic C918/SS22H High Speed Dome

Power Supply : AC24V 50/60Hz
Power Consumption : Indoor dome : 15W
Outdoor dome : 35W
Sync system : Internal / External selectable
Preset : 128 preset
Auto tour : 6 Pattern : 40s
Alarm : 4 channels input & 1 channel output
Privacy masking : 6 (some model only)
Zoom-rotation Interaction : Control speed auto
adjust according
to the focus length
Auto flip : Rotate 180° when camera tilts to the
vertical position
Auto pan scan : 360°
Programmable Pan speed : 0° ~ 300° /s
Pan rotation range : 360° continues
Tilt range : Tilt 90° Tilt speed : 0° ~ 120° /s
Control mode : RS485
Baud Rate : 2400/4800/9600/19200 bps
Fan & heater : Fan & heater auto-start
(only outdoor dome)
Environment temp : Indoor dome : 0 °C ~ +40 °C
Out door dome : -35 °C ~ +55 °C